



- L:
- CBL-U3.1AC-0.5m 500mm±10mm
 - CBL-U3.1AC-0.6m 600mm±10mm
 - CBL-U3.1AC-0.7m 700mm±10mm
 - CBL-U3.1AC-0.8m 800mm±10mm
 - CBL-U3.1AC-1m 1000mm±10mm
 - CBL-U3.1AC-2m 2000mm±20mm
 - CBL-U3.1AC-3m 3000mm±20mm

PIN OUT		
USB A(M)		USB C(M)
1 —————	RED	————— A4,A9,B4,B9
2 ————X———	WHITE	————— A5
3 ————X———	GREEN	————— A6
4 —————	BLACK	————— A1,A12,B1,B12
5 —————	BLUE	————— B10
6 —————	BLACK	————— B11
7 ————●———	DRAIN WIRE	————— A1,A2
8 ————●———	BROWN	————— A2
9 ————●———	ORANGE	————— A3
SHELL ————	BRAID	————— SHELL

No	MATERIALS LIST:
1.	CABLE:UL2725 (30AWG*1PR+D+AM)x4C+32AWG*4C+32AWG*2C +26AWG*2C+AL+D+B OD:4.8mm PVC JACKET COLOR:BLACK
2.	CONNECTOR:USB 3.0 A/M, 9P, BLUE INSULATOR, SOLDER TYPE, NICKEL PLATED SHELL
3.	CONNECTOR:USB 3.1 C/M, 22P, BLACK INSULATOR, SOLDER TYPE, NICKEL PLATED SHELL
4.	PVC MOLDED HOUSING, BLACK COLOR

Jargy part no.	Client part no.	Approved	SCALE	UNIT
CBL-U3.1AC-Xm			1 : 1	mm
Drawing Name		Drawn	Date	REV.
USB 3.1 A to C Cable M/M		<i>Kevin Hsu</i>	2015/08/06	1.0